

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 June 2003 (26.06.2003)

PCT

(10) International Publication Number
WO 03/051676 A1

(51) International Patent Classification⁷: B60R 13/08

(72) Inventor; and

(21) International Application Number: PCT/JP02/14269

(75) Inventor/Applicant (for US only): BELPAIRE, Vincent
[BI/BE], Rue de Bourgogne 37, B-1190 Forest (BE).

(22) International Filing Date:
14 December 2002 (14.12.2002)

(74) Agent: ISLER, Jörg; c/o Sika Schweiz AG, Tüffenwies
16, CH-8048 Zürich (CH).

(25) Filing Language: English

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MY, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SI, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English


(30) Priority Data:
01130188.4 19 December 2001 (19.12.2001) EP

(71) Applicant (for all designated States except US): SIKA
SCHWEIZ AG [CH/CI]; Tüffenwies 16 - 22, CH-8064
Zürich (CH).

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: BAFFLE EQUIPPED WITH FLAP ASSEMBLY



(57) Abstract: The present invention relates to an acoustic baffle device for sealing a cavity of a vehicle body at a predetermined cross section of the cavity, comprising a piece of sealing material that is formed in a shape corresponding to but being smaller than the shape of the cross section of the cavity. The acoustic baffle device of the invention is characterized in having a flap assembly having a lower neck defining a passage for a flexible tube or a similar device, said lower neck having a flap secured in closed position by a locking device and being connected preferably to the lower end of the lower neck through means that permit the reversible opening of the above-defined passage. Furthermore, the present invention relates to a flap assembly useful for such an acoustic baffle device, and to a process for sealing a cavity of a vehicle body at a predetermined cross section of the cavity.

WO 03/051676 A1



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IL, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

with international search report

Declarations under Rule 4.17:

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

5

BAFFLE EQUIPPED WITH FLAP ASSEMBLY

10

Technical Field

The present invention relates to an acoustic baffle device for sealing a cavity of a vehicle body at a predetermined cross section of the cavity.

15

Background Art

Especially in case of cars being equipped with sun roofs, after having sealed, e.g., the pillar cavities of the vehicle body during car manufacturing process by means of acoustic baffles, drain tubes may be introduced in said cavities additionally, in order to remove and dispose the rain water accumulated around the sun roof. If, however, such an introduction of drain tubes is possible, this step usually damages the baffle, tending thereby to affect or even destroy at least partially its acoustic dampening effect. Furthermore, according to baffle arrangements corresponding to the state of the art, a possible solution for that problem is to include preconstructed gaps, slits or holes in the baffle, capable of and suitable for being opened by any subsequent mechanical touch. A significant drawback of such modified baffle systems is, however, that even slight flow of certain chemical substances as used, e.g., in the stage of electro coating bath (EC-bath) for vehicle body treatment could result in an undesired opening of said gaps, holes or slits, resulting consequently in an undesired deterioration of the acoustic dampening performance of the baffle. Furthermore, when using the acoustic baffle devices according to the state of

the art, as a consequence of the above discussed drawbacks it is particularly not possible to introduce a drain tube or a similar device from a larger distance and/or in a non accessible area without any tools and/or additional manual operation.

5

Technical Problem and Solution

There is consequently a strong need for an acoustic baffle system avoiding such disadvantages according to the state of the art, i.e., a device that makes possible the passage of a drain tube (or any other device, electric cables, etc....) in cavities, preferably pillar cavities of cars after the expansion of sealing material and that furthermore guarantees the unrestricted acoustic performance profile of the baffle when no such tube or similar device is introduced in this pillar. This problem is solved by the technical teaching of the present invention, providing an acoustic baffle device being equipped with a flap assembly that makes possible the passage of a drain tube (or any other, similar device; electric cables, etc....) during any stage of car manufacturing, preferably after the expansion of sealing material, and that furthermore guarantees the unrestricted, acoustic performance profile of the baffle when no tube is introduced in the pillar, i.e., the flap remains in closed position.

It is therefore the object of the present invention to provide an acoustic baffle device having a flap assembly that makes possible the passage of a drain tube (or any other device, electric cables, etc....) during any stage of car manufacturing, preferably after the expansion of sealing material and that guarantees furthermore the unrestricted acoustic performance profile of the baffle when no tube is introduced in the cavity. In the latter case, the flap remains in closed position, even when being affected by a flow during any vehicle body treatment step or post manufacturing treatment stages.

According to a preferred embodiment, it is another object of the present invention to provide an acoustic baffle device having a flap assembly that

makes possible the introduction of a drain tube from a larger distance, in non accessible area, without any tools or additional operation by hand.

According to the present invention, an acoustic baffle device is provided for
5 sealing a pillar cavity of a vehicle body at a predetermined cross section of the cavity. The device comprises a piece of sealing material being preferably heat expandable, which sealing material is formed in a shape corresponding to but being smaller than the shape of the cross section of the cavity. The sealing material has preferably an activation temperature corresponding to expansion
10 temperature of the material. Preferably, a support element can be provided beneath or around or in the piece of sealing material for supporting it.

The acoustic baffle device is equipped with a „flap assembly“, which is preferably secured to the support or co-injected with it. This flap assembly
15 includes a lower neck defining a passage for a drain tube (or any other, similar device) that may be introduced in a pillar. The lower neck has a flap positioned preferably at its end and being secured in closed position by a flexible locking means, preferably a hook. The flap is connected to the lower neck preferably in the area of the lower end of the neck through means that permit the opening
20 and the passage of a tube, preferably by means of a hinge. The flap assembly may preferably also include an upper neck that guides the introduction of drain tube and makes possible the introduction from a larger distance.

25 **Disclosure of the invention**

The present invention provides an acoustic baffle device for sealing a cavity of a vehicle body at a predetermined cross section of the cavity, comprising a piece of sealing material that is formed in a shape corresponding to but being
30 smaller than the shape of the cross section of the cavity. The acoustic baffle device of the invention is characterized in having a flap assembly having a lower neck defining a passage for a flexible tube or a similar device, said lower neck having a flap secured in closed position by a locking device and being

connected to preferably the lower end of the lower neck through means that permit the reversible opening of the above-defined passage. Preferably, the sealing material is heat expandable. More Preferably, the sealing material has an activation temperature corresponding to the expansion of said material, most preferably in the range of between 130 °C and 210 °C. Particularly, the sealing material is heat expandable, foaming polyethylene and/or Ethyl-Vinylacetat-Copolymer (EVA).

According to a preferred embodiment, the acoustic baffle device is equipped with a support element provided beneath or around or in the piece of sealing material for supporting the same. More preferably, the support element is based on any heat resistant type of common plastic, preferably polyamide, most preferably polyamide 6, polyamide 6,6, polyamide 11, polyamide 12 or a mixture of themselves. The expression "heat resistant" means here that the material is completely resistant towards a temperature in the range of between 130 °C to 210 °C.

Preferably, the flap assembly is secured to the support element or co-injected with it, and the lower neck is positioned at the end of the flap assembly. The locking device securing the flap in closed position is preferably a flexible hook, and the means connecting the flap to preferably the end of the lower neck is preferably a hinge. The flexion of the locking device and opening of the flap is activated by the pressure of the tube between the wall of the lower neck and the locking device itself when the tube is introduced in the assembly.

According to another preferred embodiment of the acoustic baffle device, the flap assembly also has an upper neck that guides the introduction of a drain tube or any similar device from a larger distance, most preferably without any additional, manual operation.

Furthermore, according to the technical teaching of the present invention is provided a flap assembly useful for an acoustic baffle device for sealing a cavity of a vehicle body at a predetermined cross section of the cavity, having a

lower neck defining a passage for a flexible tube or a similar device, said lower neck having a flap secured in closed position by a locking device and being connected to the lower neck, preferably in the range of its lower end through means that permit the reversible opening of the above-defined passage.

- 5 Preferably, the flap assembly is secured to the support element of an acoustic baffle device or co-injected with it, and preferably the lower neck is positioned at the end of the flap assembly. Furthermore, preferably the locking device securing the flap in closed position is a flexible hook, and the the means connecting the flap to the lower end of the neck is preferably a hinge.

10

According to a preferred embodiment, said flap assembly also has an upper neck that guides the introduction of a drain tube or a similar device from a larger distance, more preferably without any ,additional, manual operation.

- 15 Preferably, the flap assembly is manufactured by an injection moulding process, more preferably it is manufactured in the form of one single, moulded piece. Most preferably, the flap assembly is based on any heat resistant type of common plastic, preferably polyamide, most preferably polyamide 6, polyamide 6,6, polyamide 11, polyamide 12 or a mixture of themselves.

20

Furthermore, according to the present invention is provided a process for sealing a cavity of a vehicle body at a predetermined cross section of the cavity while permitting the reversible opening of a passage for a flexible drain tube or a similar device, comprising a step of introducing an acoustic baffle device as described above in at least one of the cavities, preferably pillar cavities of a vehicle body. Preferably, in such a process the flap assembly as described above is secured to the support element of the above-described acoustic baffle device or co-injected with it.

25

- 30 Most preferably, the above-described flap assembly of the invention may be used in one of the stages of a process as described in above section.

Based on the technical teaching of the present invention, drain tubes may be assembled in any vehicles, preferably such vehicles being equipped with a sun roof. Drain tubes preferably could be assembled during the so called „body in white step“ of baffle assembling (i.e., before expansion of sealing material) or during the assembly as such (i.e., after expansion of sealing material). According to the teaching of the invention, the angle between the axis of the acoustic baffle device (and also the flat assembly, consequently), on the one hand, and the axis of the cavity, on the other hand, can be defined easily by analysing the introduction path of the drain tube. Preferably, the flap assembly of the invention is made of one single moulded piece and can be furthermore designed to be injected without any mobile parts in the mould. Preferably, the expandable sealing material can be overmoulded (dual moulding).

15 Example

The Figures 1 and 2 each provide two schematical, perspective views of a working example for an acoustic baffle device having a flap assembly corresponding to a preferred embodiment of the present invention. The Figures 3(a) and (b) each show two schematical cross sections of one and the same working example for a flap assembly according to a preferred embodiment of the present invention. Figure 3(a) represents the opened state and Figure 3(b) the closed state of this example for a cross section of a flap assembly according to the invention. Figure 4 is a schematical, perspective view representing an example for the effect of the locking device in accordance with a preferred embodiment of the flap assembly of the present invention. Figures 5 to 9 each represent different, subsequent stages of the introduction of a drain tube into a flap assembly according to an example for a preferred embodiment of the present invention in the form of schematical cross sections. The direction of the movement of the drain tube in Figures 5 to 8 is indicated by an arrow.

Claims

1. An acoustic baffle device for sealing a cavity of a vehicle body at a predetermined cross section of the cavity, comprising a piece of sealing material that is formed in a shape corresponding to but being smaller than the shape of the cross section of the cavity, **characterized in** having a flap assembly having a lower neck defining a passage for a flexible tube or any similar device, said lower neck having a flap secured in closed position by a locking device and being connected to the lower neck preferably in the range of its lower end through means that permit the opening of the above-defined passage.
2. An acoustic baffle device according to claim 1, **characterized in** that the sealing material is heat expandable.
3. An acoustic baffle device according to any of claims 1 or 2, **characterized in** that the sealing material has an activation temperature corresponding to the expansion temperature of said material, preferably in the range of between 130 °C and 210 °C.
4. An acoustic baffle device according to any of preceding claims, **characterized in** that the sealing material is heat expandable, foaming polyethylene and/or Ethyl-Vinylacetat-Copolymer (EVA).
5. An acoustic baffle device according to any of preceding claims, **characterized in** that it is equipped with a support element provided beneath or around or in the piece of sealing material for supporting the same.
6. An acoustic baffle device according to claim 5, **characterized in** that the support element is based on any heat resistant type of common plastic, preferably polyamide, most preferably polyamide 6, polyamide 6,6, polyamide 11, polyamide 12 or a mixture of themselves.

7. An acoustic baffle device according to any of claims 5 or 6, **characterized in** that the flap assembly is secured to the support element or co-injected with it.
- 5 8. An acoustic baffle device according to any of preceeding claims, **characterized in** that the lower neck is positioned at the end of the flap assembly.
- 10 9. An acoustic baffle device according to any of preceeding claims, **characterized in** that the locking device securing the flap in closed position is a flexible hook.
- 10 10. An acoustic baffle device according to any of preceeding claims, **characterized in** that the means connecting the flap to the lower neck is a hinge.
- 20 11. An acoustic baffle device according to any of preceeding claims, **characterized in** that the flap assembly also has an upper neck that guides the introduction of a drain tube or any similar device from a larger distance, preferably without any additional, manual operation.
- 25 12. A flap assembly being preferably useful for an acoustic baffle device for sealing a cavity of a vehicle body at a predetermined cross section of the cavity, having a lower neck defining a passage for a flexible tube or any similar device, said lower neck having a flap secured in closed position by a locking device and being connected to the lower neck preferably in the range of its end through means that permit the opening of the above-defined passage.
- 30 13. A flap assembly according to claim 12, **characterized in** that the flap assembly is secured to the support element of an acoustic baffle device or co-injected with it.

14. A flap assembly according to any of claims 12 or 13, **characterized in** that the lower neck is positioned at the end of the flap assembly.
15. A flap assembly according to any of claims 12 to 14, **characterized in**
5 that the locking device securing the flap in closed position is a flexible hook.
16. A flap assembly according to any of claims 12 to 15, **characterized in** that the means connecting the flap to the lower neck is a hinge.
- 10 17. A flap assembly according to any of claims 12 to 16, **characterized in** that said flap assembly also has an upper neck that guides the introduction of a drain tube or any similar device from a larger distance, preferably without any additional, manual operation.
- 15 18. A flap assembly according to any of claims 12 to 17, **characterized in** that said flap assembly is manufactured by an injection moulding process.
19. A flap assembly according to any of claims 12 to 18, **characterized in** that said flap assembly is manufactured in the form of one single, moulded
20 piece.
20. A flap assembly according to any of claims 12 to 19, **characterized in** that said flap assembly is based on any heat resistant type of common plastic, preferably polyamide, most preferably polyamide 6, polyamide 6,6, polyamide
25 11, polyamide 12 or a mixture of themselves.
21. Process for sealing a cavity of a vehicle body at a predetermined cross section of the cavity while permitting the reversible opening of a passage for a flexible drain tube or any similar device, comprising a step of introducing an
30 acoustic baffle device in accordance with any of claims 1 to 11 into at least one of the cavities of a vehicle body, preferably into at least one of the pillar cavities.

- 22.** A process according to claim 21, **characterized in** that a flap assembly according to any of claims 12 to 20 is secured to the support element of the acoustic baffle device or co-injected with it.
- 5 **23.** Use of a flap assembly according to any of claims 12 to 20 in a process according to any of claims 21 or 22.




Fig. 1




Fig. 2




Fig. 3




Fig. 4

5/9




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9

INTERNATIONAL SEARCH REPORT

Inte Application No
PCT/EP 02/14269

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60R13/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 01 24989 A (TYCO ELECTRONICS CORP) 12 April 2001 (2001-04-12) page 1, line 16 -page 4, line 29 page 11, line 4 - line 13 page 11, line 21 -page 12, line 2 figures 5A,5B,7A,7B -----	1-5, 12, 21, 23
A	EP 0 679 501 A (YMOS AG IND PRODUKTE) 2 November 1995 (1995-11-02) column 5, line 39 -column 6, line 33 figure 3 -----	1-3, 21
A	EP 0 453 777 A (ORBSEAL INC) 30 October 1991 (1991-10-30) claim 1; figure 2 -----	1-3, 21

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

S document member of the same patent family

Date of the actual completion of the international search

20 March 2003

Date of mailing of the international search report

03/04/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5018 Patentlaan 2
NL - 2260 HV Rijswijk
Tel: (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Colonna, M

INTERNATIONAL SEARCH REPORT

Inten Application No
PCT/EP 02/14269

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0124989	A	12-04-2001	WO 0124989 A1 12-04-2001
EP 0679501	A	02-11-1995	EP 0679501 A1 02-11-1995 DE 29522122 U1 18-11-1999 DE 69510417 D1 29-07-1999 DE 69510417 T2 16-12-1999 WO 9525005 A1 21-09-1995 EP 0697956 A1 28-02-1996 ES 2137505 T3 16-12-1999 JP 8510703 T 12-11-1996 US 5766719 A 16-06-1998
EP 0453777	A	30-10-1991	US 5040803 A 20-08-1991 AU 629466 B2 01-10-1992 AU 7367091 A 24-10-1991 BR 9101585 A 10-12-1991 DE 69102009 D1 23-06-1994 DE 69102009 T2 08-12-1994 EP 0453777 A2 30-10-1991 ES 2053227 T3 16-07-1994 JP 4228381 A 18-08-1992 KR 9409348 B1 07-10-1994 MX 169127 B 22-06-1993